

Appliance - Split type air conditioner		Directive 2009/125/EC
Supplier	Toshiba Carrier Corporation	
Outdoor unit	RAS-13J2AVSG-E1	
Indoor unit	RAS-B13N4KVRG-E	

Refrigerant		
Type	R32	
Global Warming Potential	GWP kgCO2eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Sound power level		Cooling	Heating
Outdoor unit	dB	59	61
Indoor unit	dB	56	56

Cooling		
Energy efficiency class	A+++	
Design load	Pdesignc kW	3.5
Seasonal efficiency	SEER	8.70
Seasonal electricity consumption (*)	Qce kWh/annum	142

Heating		Average climate	Colder climate	Warmer climate
Energy efficiency class		A+++	-	A+++
Design load	Pdesignh kW	3.2	-	3.4
Seasonal efficiency	SCOP	5.10	-	6.30
Seasonal electricity consumption (*)	Qhe kWh/annum	876	-	752
Back up heating capacity	kW	0.270	-	0.000

Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.

Tj = -7 °C	Pdh kW	2.83	-	-
Tj = +2 °C	Pdh kW	1.72	-	1.72
Tj = +7 °C	Pdh kW	1.11	-	1.11
Tj = +12 °C	Pdh kW	1.17	-	1.17
Tj = bivalent temperature	Pdh kW	2.83	-	3.40
Tj = operation limit temperature	Pdh kW	3.10	-	3.10

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

Contact details

Carrier RLC Europe S.A.S - Route de Thil, 01120, Montluel,France