

Appliance - Split type air conditioner			Directive 2009/125/EC
Supplier	Toshiba Carrier Corporation		
Outdoor unit	RAS-18J2AVSG-E		
Indoor unit	RAS-18J2KVSG-E		

Refrigerant			
Type	R32		
Global Warming Potential	GWP	kgCO2eq	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Sound power level		Cooling	Heating
Outdoor unit	dB	63	63
Indoor unit	dB	57	57

Cooling			
Energy efficiency class	A++		
Design load	Pdesignc	kW	5.0
Seasonal efficiency	SEER		7.30
Seasonal electricity consumption (*)	Qce	kWh/annum	242

Heating		Average climate	Colder climate	Warmer climate
Energy efficiency class		A++	-	A+++
Design load	Pdesignh	kW	4.3	2.3
Seasonal efficiency	SCOP	4.60	-	6.00
Seasonal electricity consumption (*)	Qhe	kWh/annum	1309	540
Back up heating capacity		kW	0.870	0.000

Declared capacity for heating, at indoor temperature 20°C and outdoor temperature Tj.

Tj = -7 °C	Pdh	kW	3.80	-	-
Tj = +2 °C	Pdh	kW	2.32	-	2.32
Tj = +7 °C	Pdh	kW	1.49	-	1.49
Tj = +12 °C	Pdh	kW	1.74	-	1.74
Tj = bivalent temperature	Pdh	kW	3.80	-	2.32
Tj = operation limit temperature	Pdh	kW	2.80	-	2.80

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

Contact details

Carrier RLC Europe S.A.S - Route de Thil, 01120, Montluel,France